



8 ESPECIFICAÇÕES TÉCNICAS / TECHNICAL DATA / SPECIFICATIONS TECHNIQUES / TECHNISCHE DATEN

	HONDA GX100 DKR	HONDA GX120 DKR	ROBIN EC12 D	ROBIN EH12 D	YANMAR L40 AE
COMBUSTÍVEL (L) FUEL (L) COMBUSTIBLE (L) BRENNSTOFF (L)	SEM CHUMBO (2,7)	SIN PLOMO (2,7)	MIX 50:1 (2,7)	SIN PLOMO (2,7)	GAS-OIL (2,7)
ÓLEO MOTOR (L) ENGINE OIL (L) HUILE MOTEUR (L) MOTORENÖL (L)	SAE 10W/40 (0,6)	SAE 10W/40 (0,3)	SAE 10W/40	SAE 10W/40 (0,4)	SAE 10W/40 (0,8)
POTÊNCIA NOMINAL NOMINAL POWER PUISSANCE NOMINALE NENNLEISTUNG	3 kW (4 HP)	3 kW (4 HP)	3 kW (4 HP)	2,6 kW (3,5 HP)	3,1 kW (4,1 HP)
VELA SPARK PLUG BOUGIE ZÜNDKERZE	NGK CR5HSB DENSO U16FSR-UB	NGK BP4ES DENSOW14EP-U	NGK BM6A CHAMPION CJ8	NGK B6ES CHAMPION N4C	----
ENTREFERRO GAP ENTREFER LUFTSPALT	0,6 mm - 0,7 mm	0,7 mm - 0,8 mm	0,6 mm - 0,7 mm	0,6 mm - 0,7 mm	----
R.P.M. R.P.M. TR-MN U-MN	4000 rpm ± 50	3600 rpm ± 50	3600 rpm ± 100	3600 rpm ± 50	3600 rpm ± 50
RALENTI IDLING RÉGIME RALENTI LEERLAUFDREHZAHN	1500 ± 150 r.p.m.	1500 ± 150 r.p.m.	2100 ± 100 r.p.m.	1600 ± 150 r.p.m.	1500 ± 150 r.p.m.

ESPECIFICAÇÕES	PC60 H 4T	PC65 R 2T	PC70 R 4T	PC80 H 4T	PC85 Y D
DIMENSÕES DIMENSIONS DIMENSIONS DIMENSIONEN	770x398x103 038	770x398x103 8	770x398x103 8	770x398x103 8	770x398x103 8
PESO SEM COMBUSTÍVEL (Kg) WEIGHT WITHOUT COMBUSTIBLE (Kg) POIDS SANS COMBUSTIBLE (Kg) GEWICHT (Kg)	69	72	79	75	85
DIMENSÕES PÉ FOOT DIMENSIONS DIMENSIONS DU PIED FUSSGRÖSSE	333x280	333x280	333x280	333x280	333x280
ELEVAÇÃO DO PISÃO (mm) IMPACT COURSE HEIGHT (mm) PARCOURS DE FRAPPE (mm) SPRINGWEG (mm)	60	65	70	70	70
NÚMERO DE GOLPES POR MINUTO NUMBER OF BLOWS BY MINUTE FREQUENCE D'IMPACTS PAR MINUTE EINSCHLAGSFREQUENZ	700	650	650	650	650
MOTOR ENGINE MOTEUR MOTOR	HONDA GX120 DKR	ROBIN EC12 D	ROBIN EH12 DU	HONDA GX120 DKR	YANMAR L40 AE
LUBRIFICANTE MÁQUINA (L) MACHINE OIL (L) HUILE POUR MACHINE (L) MASCHINENÖL (L)	MORLINA 100 (1.8 L.) DENSOLINA 100 (1.8 L.)				