



Features

- Water tank with low level cut out
- Current overload protection
- 7.5 m power lead with cable reel (599 TST: 5 m)
- Shock absorbing buffers
- Parking brake
- Brass pump head
- Ceramic-coated stainless steel pump pistons
- Continuously adjustable pressure control
- Dry-run safety
- Total-Stop system with delayed motor cut-out
- Starlet trigger gun with safety catch
- Stainless steel lance with flat jet nozzle
- 20m Steel braided high-pressure hose

Technical Specifications

Kränzle Quadro 599 TST / 799 TST

**SUPERIOR
GERMAN
QUALITY**



Details	599 TST	799 TST
Operating pressure	30-150 bar	30-180 bar
Max. admissible overpressure	165 bar	200 bar
Water output	10l/min	13l/min
Nozzle size (flat jet)	20035	20045
Dirtkiller lance	Additional	Additional
Max. inlet water temperature	60°C	60°C
Hose drum	Yes	Yes
Chemical injector	Additional	Additional
Connected load - 50Hz	230V, 14 A	400V, 8.5 A
Motor speed	1 400 r.p.m	1 400 r.p.m
Power input/output	3.3 kW/2.4 kW	5.5 kW/4 kW

Specialist equipment for professional application



Features

- Water tank with low level cut out
- Current overload protection
- 7.5 m power lead with cable reel (599 TST: 5 m)
- Shock absorbing buffers
- Parking brake
- Brass pump head
- Ceramic-coated stainless steel pump pistons
- Continuously adjustable pressure control
- Dry-run safety
- Total-Stop system with delayed motor cut-out
- Starlet trigger gun with safety catch
- Stainless steel lance with flat jet nozzle
- 20m Steel braided high-pressure hose

Technical Specifications

Kränzle Quadro 899 TST

**SUPERIOR
GERMAN
QUALITY**



Details	899 TST
Operating pressure	30-150 bar
Max. admissible overpressure	170 bar
Water output	15l/min
Nozzle size (flat jet)	2506
Dirtkiller lance	Additional
Max. inlet water temperature	60°C
Hose drum	Yes
Chemical injector	Additional
Connected load - 50Hz	400V, 8.5 A
Motor speed	1 400 r.p.m
Power input/output	5.5 kW/4 kW

Specialist equipment for professional application