

High-performance and robust

The K 2000 series

- Single-part Roto-Mold-chassis and therefore extremely stable and robust
- Integrated trolley takes steps and rough ground in its stride
- Integrated hose drum with foldable crank (TS T)
- 5 m power lead with cable reel
- Dirtkiller lance with stainless steel pipe, Vario-Jet lance, lance with stainless steel pipe with fully adjustable spray angle from pencil to wide fan as well as high and low pressure
- Storages for trigger gun with safety catch and lances
- Total-Stop system
- Low pressure detergent



K 2000 TS T with hose drum



K 2000 TS
without hose drum



Technical specifications	K 2160 TS / TS T	K 2195 TS / TS T	K 2175 TS / TS T
Ord. no. without hose drum	41,780 1	41,784 1	41,782 1
Ord. no. with hose drum	41,781 1	41,785 1	41,783 1
Operating pressure, continuously adjustable	30-140 bar / 3-14 MPa	30-180 bar / 3-18 MPa	30-160 bar / 3-16 MPa
Max. admissible overpressure	160 bar / 16 MPa	195 bar / 19.5 MPa	175 bar / 17.5 MPa
Water output	11 l/min (660 l/h)	8 l/min (480 l/h)	12 l/min (720 l/h)
Motor speed	1,400 rpm	1,400 rpm	1,400 rpm
Connected load	230 V, 14 A, 50 Hz	230 V, 14 A, 50 Hz	400 V, 6,7 A, 50 Hz
Power intake / Power output	3.2 kW / 2.4 kW	3.2 kW / 2.4 kW	3.3 kW / 2.6 kW
Weight without / with hose drum	37 kg / 39.5 kg	37 kg / 39.5 kg	37 kg / 39.5 kg
Features & Equipment	Ord. no.	Ord. no.	Ord. no.
Steel braided high-pressure hose NW 6, without hose drum	10 m (43,416)	10 m (43,416)	10 m (43,416)
Steel braided high-pressure hose NW 6, with hose drum	15 m (48,015)	15 m (48,015)	15 m (48,015)
Tigger gun with safety catch M2000	(12,480)	(12,480)	(12,480)
Dirtkiller lance with stainless steel pipe	(41,570-042)	(41,570-03)	(41,570-042)
Vario-Jet lance with stainless steel pipe	(41,156 8-042)	(41,156 8-03)	(41,156 8-042)